



86BM66AE

86" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense's BM66AE Digital Signage Displays (43"- 86") are perfectly fit for public transport and retail locations. Their slim body design will make them blend into their surrounding and make your on-screen messaging stand out. Their vivid and vibrant colours immerse viewers and will effectively provide them with the information they are looking for.

All this with the flexibility and reliability that are required for round-the-clock broadcasting locations due to light sensors, intelligent temperature control and dual-core SOC technology for PC-less offline or cloud based content management. You can rest assure your content will be delivered 24/7 in an elegant, vibrant and reliable way.

Highlights



Smart CMS

Hisense's CMS platform allows you to edit and arrange playlists, making content management easy and user-friendly. It supports all rich media content in synchronous playback over a multitude of commercial displays.



Landscape & portrait

Both landscape and portrait orientations are possible, providing you with endless creative and functional possibilities to fulfil your commercial or informative goals.



178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view BM66AE displays from diverse angles while passing by.



Customization

Hisense's BM66AE displays support a variety of on-screen customisations such as custom startup logo, startup animation, wallpapers and many more.



Round-the-clock operation

Designed with dual-core System on Chip (SoC) technology the Hisense BM66AE series can be used as reliable digital signage displays for both offline and cloud based content 24 hours a day, 7 days a week.



4K Ultra HD

The 4K Ultra HD picture quality* ensures perfect colour and rich details in all possible broadcasting surroundings, ranging from shops, to restaurants and office buildings.



500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Automatic time zone

When connected to the Internet each display will automatically synchronise to its local timezone. Making sure scheduled media broadcast is always in sync.



Specifications

Digital Display Panel

Backlight	ELED
Size	86
Resolution	3840 x 2160
Refresh rate	120Hz
Color	1.07B
Brightness	500nits
Contrast(typ)	1100:1 (typ)
Response time(typ)	8ms
Viewing angle(Min.)	178°/178°
Color gamut	72%
Haze	28%
Orientation	Landscape & Portrait
MTBF	50000hrs
Operation Hours	7Day*24Hour

Power

Input	AC 100~240V(50/60Hz)
Power Consumption	300W(Max)
Standby consumption	<0.5W

Physical

Bezel Color	Black
Set Dimension(W×H×D)	1927.2mm ×1098mm × 72.1mm
Bezel width(T/L/R/B)	15.3mm(T/B/L/R)
Net Weight	62kg
Packing Dimension (W×H×D)	2127mm × 1312mm x 297mm
Packed Weight	76.1kg
VESA	600mm x 400mm

System

OS	Android 9.0
DDR	2G
ROM	16G
Language	English/Chinese

Connectivity

WIFI	Yes
LAN	1xRJ45
INPUT	1xUSB 1xDVI 2xHDMI 1xDP 1xVGA 1xRS232
Output	1xAudio 1xHDMI 1xRS232

Certification

Standard Certification	CB,CE,ERP
EAN	-
Energy Table	86BM66AE



Speaker

Built in speaker	15W x2
------------------	--------

Control Method

Remote	Yes
RS232	Yes

Environment

Temperature	Storage: -20°~60°
	Operation: 0°~40°
Humidity	Storage: 10%~90%
	Operation: 10%~80%

Media Player compatibility

OPS Type Compatible	Yes
---------------------	-----

What's in the box

Basic	Power cord
	Remote control
	Battery
	Logo

Dimensions

